

ICE-B3H/LV & ICE-B3H/M



- Monochrome Camera
- 1/3" CCD
- High Resolution 580 lines

Camera Features

Sensor 1/3" Sony Super HAD CCD™

Video Processing Analogue

Effective Pixels 752 (H) x 582 (V)

Sensitivity 0.07 lux; for usable picture (40% video) with AGC on; lens at F1.2

Resolution 580 TVL

Video Output 1V p-p composite video via 75Ω BNC connector

Signal to Noise Ratio Better than 50dB

AGC On / Off, max <28dB

Electronic Iris 1/50s~1/100,000s; On / Off

Backlight Compensation On/Off, centre weighted

Gamma Correction 0.45

Synchronisation System Internal or Line lock (±120° adjustment)



ICE-B3H/LV & ICE-B3H/M

Lens Options

Lens Mount and Focus 'C' or 'CS' mount, thumbwheel adjustment

Auto Iris Lens DC and Video via 4 pin socket

Direct Drive (DC iris) 4-pin square type socket on the side of the camera. DC level is user defined

via a potentiometer located on the rear of the camera

Power Supply

Low Voltage Source AC: 24V ±15% @ 50Hz DC: 12V -10% +15%

Mains Source 98~260V AC 50Hz

Consumption Less than 4.2W including 50mA DC lens

Input Connector /LV: 2-way terminal connector on rear panel

/M: 2m twin conductor mains cord (Class 2 product)

Power Indicator Blue LED on rear panel

Mechanical

Camera Mount 1/4" 20 UNC top and bottom Dimensions (mm) $123 \text{ (L)} \times 60 \text{ (H)} \times 52 \text{ (W)}$

Weight /LV: 0.35kg, shipping weight 0.45kg

/M: 0.5kg, shipping weight 0.6kg

Material Cast Zinc lens mount; zintec case; V0 ABS trim


Environmental

Operating Temperature -10 to +50°C (14 to 122°F)

Operating Humidity 20% to 80% relative humidity, non condensing

Storage Temperature -10 to +70°C (14 to 158°F)

Storage Humidity 20% to 90% relative humidity, non condensing







ICE-B3H/M



Super HAD CCD™ is a trademark of the Sonv Corporation. Price and specification are subject to change without notice

