ICE-B3M/LV & ICE-B3M/M



- Monochrome Camera
- 1/3" CCD
- Medium Resolution 380 lines

Camera Features

íce

Sensor	1/3" Sony Super HAD CCD™
Video Processing	Analogue
Effective Pixels	500 (H) x 582 (V)
Sensitivity	0.06 lux; for usable picture (40% video) with AGC on; lens at F1.2
Resolution	380 TVL
Video Output	1V p-p composite video via 75 Ω BNC connector
Signal to Noise Ratio	Better than 50dB
AGC	On / Off, max <28dB
Electronic Iris	1/50s~1/100,000s; On / Off
Backlight Compensation	On/Off, centre weighted
Gamma Correction	0.45
Synchronisation System	Internal or Line lock (±120° adjustment)



Lens Options

Lens Mount and Focus Auto Iris Lens Direct Drive (DC iris) 'C' or 'CS' mount, thumbwheel adjustmentDC and Video via 4 pin socket4-pin square type socket on the side of the camera. DC level is user defined via a potentiometer located on the rear of the camera

Power Supply

Low Voltage Source	
Mains Source	g
Consumption	L
Input Connector	/
	/
Power Indicator	E

AC: 24V ±15% @ 50Hz DC: 12V -10% +15% 98~260V AC 50Hz Less than 4.2W including 50mA DC lens /LV: 2-way terminal connector on rear panel /M: 2m twin conductor mains cord (Class 2 product) Blue LED on rear panel

Mechanical


Camera Mount
Dimensions (mm)
Weight

1/4" 20 UNC top and bottom
123 (L) x 60 (H) x 52 (W)
/LV: 0.35kg, shipping weight 0.45kg
/M: 0.5kg, shipping weight 0.6kg
Cast Zinc lens mount; zintec case; V0 ABS trim

Material

Environmental

Operating Temperature Operating Humidity Storage Temperature Storage Humidity -10 to +50°C (14 to 122°F)
20% to 80% relative humidity, non condensing
-10 to +70°C (14 to 158°F)
20% to 90% relative humidity, non condensing



ICE-B3M/LV



ICE-B3M/M



Super HAD CCD™ is a trademark of the Sony Corporation. Price and specification are subject to change without notice.

Unit 1 Castlehill, Horsfield Way, Bredbury Park Industrial Estate, Stockport, Cheshire SK6 2SU, UK. Tel: +44 (0)161 406 6611 Fax: +44 (0)161 406 8988 sales@baxall.com www.baxall.com

