

ICE-CM3M/LV & ICE-CM3M/M



- DSP Colour/Mono Camera
- 1/3" CCD
- Medium Resolution 330 lines

Camera Features

Sensor	1/3" Sony Super HAD CCD™
Video Processing	DSP
Effective Pixels	500 (H) x 582 (V)
Sensitivity	0.6 lux; for usable picture (40% video) with AGC on; lens at F1.2
Resolution	330 TVL
Video Output	1V p-p composite video via 75Ω BNC connector
Signal to Noise Ratio	Better than 50dB
Auto White Balance	2,500K ~ 9,500K
AGC	On / Off, max <28dB
Electronic Iris	1/50s~1/100,000s; On / Off
Backlight Compensation	On/Off, centre weighted
Gamma Correction	0.45
Synchronisation System	Internal or Line lock (±180° adjustment)



SPECIFICATION

ICE-CM3M/LV & ICE-CM3M/M

Lens Options

Lens Mount and Focus	'C' or 'CS' mount, thumbwheel adjustment
Auto Iris Lens	DC and Video via 4 pin socket
Direct Drive (DC iris)	4-pin square type socket on the side of the camera. DC level is user defined via a potentiometer located on the rear of the camera

Power Supply


Low Voltage Source	AC: 24V \pm 15% @ 50Hz DC: 12V -10% +15%
Mains Source	98~260V AC 50Hz
Consumption	Less than 4.2W including 50mA DC lens
Input Connector	/LV: 2-way terminal connector on rear panel /M: 2m twin conductor mains cord (Class 2 product)
Power Indicator	Blue LED on rear panel

Mechanical


Camera Mount	1/4" 20 UNC top and bottom
Dimensions (mm)	123 (L) x 60 (H) x 52 (W)
Weight	/LV: 0.35kg, shipping weight 0.45kg /M: 0.5kg, shipping weight 0.6kg
Material	Cast Zinc lens mount; zintec case; V0 ABS trim

Environmental

Operating Temperature	-10 to +50°C (14 to 122°F)
Operating Humidity	20% to 80% relative humidity, non condensing
Storage Temperature	-10 to +70°C (14 to 158°F)
Storage Humidity	20% to 90% relative humidity, non condensing



ICE-CM3M/LV



ICE-CM3M/M



BAXALL
LIMITED

Super HAD CCD™ is a trademark of the Sony Corporation. Price and specification are subject to change without notice.

Unit 1 Castlehill, Horsfield Way, Bredbury Park Industrial Estate,
Stockport, Cheshire SK6 2SU, UK.
Tel: +44 (0)161 406 6611 Fax: +44 (0)161 406 8988
sales@baxall.com www.baxall.com

