

# **ICED-DN3U39**



- DSP Day/Night Dome Camera
- Movable Filter
- 1/3" CCD
- Ultra Resolution 540 lines
- Integrated 3.6~9mm Varifocal Lens
- 3-axis GyroView Set Up
- Ceiling/surface Mount

### Camera Features

Sensor	1/3" Sony Super HAD CCD™
Video Processing	DSP
Effective Pixels	752 (H) x 582 (V)
Sensitivity	1.0 / 0.15 lux; for usable picture (40% video) with AGC on; lens at F1.6, no bubble
Resolution	540 TVL
Video Output	$1V p-p$ composite video via $75\Omega$ BNC connector, plus extra video output on front for optional service connector (Product Code ICED-SERV)
Signal to Noise Ratio	50dB
Auto White Balance	2,500K ~ 9,500K
AGC	On/Off, max <28dB
Electronic Iris	1/50s ~ 1/100,000s; On/Off
Backlight Compensation	On/Off, centre weighted
Gamma Correction	0.45
Synchronisation System	Internal or Line lock (±180° adjustment)



# **ICED-DN3U39**

#### **Lens Options**

Lens Mount and Focus

Integrated 3.6~9mm Varifocal with DC iris, F1.6

### **Power Supply**

Low Voltage Source Consumption Input Connector AC: 24V ±15% @ 50Hz; DC: 12V ±10% Less than 3.7W normal use 2-way screw terminal connector


#### Mechanical

Dimensions (mm)	120 (L) x 120 (W) x 110 (H)
Weight	0.3kg, shipping weight 0.4kg
Material	Grey ABS. Black available on request. Clear polycarbonate bubble. Other options available on request.
Installation Mount	Ceiling: via integral fixing clamps (removable shroud) Surface: via fixing screws provided


#### Environmental

Operating Temperature Operating Humidity Storage Temperature Storage Humidity

-10 to +50°C (14 to 122°F)
20% to 80% relative humidity, non condensing
-20 to +60°C (-4 to 140°F)
20% to 90% relative humidity, non condensing



3-axis GyroView (shown here with ceiling mount)



Rear view of dome base



Super HAD CCD™ is a trademark of the Sony Corporation. Price and specification are subject to change without notice.

Unit 1 Castlehill, Horsfield Way, Bredbury Park Industrial Estate, Stockport, Cheshire SK6 2SU, UK. Tel: +44 (0)161 406 6611 Fax: +44 (0)161 406 8988 sales@baxall.com www.baxall.com

